

Palm Grip

B30



The Palm Grip B30 has different equipment options for many requirements. It is compatible with our Multi-axis Controller or mounted on Hydraulic Drives. The Palm Grip has a highly flexible single wire (0,1 mm², 450 mm long). The mounting piece for the drive rod can be supplied with a tapped hole 12 mm (standard) or 10 mm.

Technical data

Operating temperature	-40°C to +85°C
Degree of protection	Control element up to IP67
Contact complement	1,5A 24 V DC 13 (*1 0,1A 24 V DC13)



Example

	B30	-2D	W	SR	SE	S12	H13	-X
Basic unit								
B30	Palm Grip							
Digital actuating element								
D	Push Button KDA21 *1							
	Colour: red, black, yellow, green, blue, white, orange							
HD	Hall-push Button (see page 167)							
W	Rocker switch momentary (T) or maintained (R), colours: red, black, yellow, blue, white							
	Mechanical functions: T-0-T, 0-T, R-0-T, R-0-R, 0-R, R-R							
SR	Sliding switch R-O-R							
ST	Sliding switch T-0-T							
SE	Sensor Button capacitive with external control electronics							
S	Sensor Button capacitive without external control electronics							
	(Consistent with V85 / VV85 with interface E1xx to E6xx, E907 and V25/V27 with interfaces E3xx + E4xx)							
Analog actuating element								
S12	Hall-Thumb rocker (see page 108)							
	Output 0,5...2,5...4,5 V inverse dual							
V21	Hall-Minijoystick (see page 53)							
	Output 0,5...2,5...4,5 V inverse dual							
HK	Hall-cross Switch (see page 164)							
H13	Hall-Rotary Grip							
	Output 0,5...2,5...4,5 V inverse dual							
Special model								
X	Special / customer specified							

B30

Push button
installed Pos. 1 - 8 +11
Rocker switch
installed Pos. 9+10

