

Crane Control Unit

KST19 swiveling



The KST19 is an ergonomically designed swiveling crane control chair which provides a high degree of comfort.

Equipment boxes:

The equipment boxes are vertically and horizontally adjustable. The arrangement of the joysticks, indicators and control devices is customised according to customer specifications. Cabling is carried out through a cross-member in the traverse. (Terminal block)

Driver's seat:

As standard the KST19 is fitted with a KFS10 seat. The seat itself is fitted with a pneumatic vibration absorption system complete with weight adjustment to ensure that the comfort level is fitted with armrests and a headrest. There is the option to have the seat covered with air-permeable artificial leather.

Cross-member with swivel base:

Swivel base has zero-clearance bearing and can be locked by a friction brake.

Surface treatment:

Base coat and textured varnish
Standard colour RAL 7035 light grey, equipment boxes RAL 7016 anthracite



Example

	KST19	-U1	-M1	-F3	-LK	/	KFS 10	/	V85	/	V85	/	KL	/	X
Basic unit															
KST19	With equipment boxes														
Base unit															
U1	Swiveling 180° left, 90° right with friction brake														
U2	Swiveling 180° left, 90° right with detent														
U4	Non swiveling														
Attachments															
M1	Monitor mounting with monitor housing														
M2	Monitor mounting with monitor mounting bracket														
M3	Monitor mounting without monitor housing/ -mounting bracket														
M4	Monitor mounting (Monitor < 5 kg) with monitor housing														
M5	Monitor mounting (Monitor < 5 kg) with mounting adapter														
F3	Footrest KBF/716														
H	Heater 2 x 2 kW with ventilator														
LK	Plate for horizontal manual adjustment for control units +/- 250 mm														
Driver's seat															
KFS10*	(Included in the delivery!)														
	*Description see Driver's seat page 248														

3

KST19 -U1 -M1 -F3 -LK / KFS10 / V85 / V85 / KL / X

Mounting for equipment boxes

V...	Multi-axis Controller (see page 1)
S...	Single-axis Controller (see page 101)
D...	Double-handle Controller (see page 80)
N...	Control-switch (see page 142)
...	More command and indicating devices (see page 218)

Wiring



KL	Without wiring, but terminal block built in each terminal
KL V	On terminal block 4 mm ² with single wire 1 mm ² each terminal
KL V	On SPS (SPS provision) with single wire 1 mm ² each terminal
KLVA	External wiring single wire highly flexible 1,5 mm ² , 5 m long each terminal

Special model

X	Special / customer specified
X ²	Special painted

Option

Radio remote control system



* adjustable