

Crane Control Unit

KST8 swiveling



The KST8 is an ergonomically designed swiveling crane control chair which provides a high degree of comfort.

Equipment boxes:

The equipment boxes are vertically and horizontally adjustable. The arrangement of the joysticks, indicators and control devices is customised according to customer specifications. Cabling is carried out through a cross-member in the traverse.

(Terminal block)

Special boxes available upon request.

Driver's seat:

As standard the KST8 is fitted with a KFS11 seat. The seat itself is fitted with a hydraulic vibration absorption system complete with weight adjustment to ensure that the comfort level is fitted with armrests and a headrest. There is the option to have the seat covered with air-permeable artificial leather.

Cross member with swivel base:

The cover of the sheet steel cross-member including the driver's seat is forward foldable. Thereby all wirings, terminals and bushings are easily accessible during commissioning and maintenance. Swivel base has zero-clearance bearing and can be locked by a friction brake.

Surface treatment:

Base coat and textured varnish

Standard colour RAL 9011 black



Example

		KST8	-U1	-M1	-F3	-LK	/	KFS 11	/	V64	/	V64.1	/	KL	/	X
3	Basic unit															
	KST8	With equipment boxes														
	Base unit															
	U1	Swiveling 180° left, 90° right with friction brake														
	U2	Swiveling 180° left, 90° right with detent														
	U3	Electric swiveling 180° left, 90° right														
	U4	Non swiveling														
	U5	Without base frame														
	Attachments															
	M1	Monitor mounting with monitor housing														
	M2	Monitor mounting with monitor mounting bracket														
	M3	Monitor mounting without monitor housing/-mounting bracket														
	F3	Footrest KBF/716														
	H	Heater 2 x 2 kW with ventilator														
	LK	Plate for horizontal manual adjustment of control units +/- 250 mm														
	Driver's seat															
	KFS11*	(Included in the delivery!)														
	KFS9*															
	KFS10*															
	KFS12*															
	*Description see Driver's seat page 248															

Technical details may vary based on configuration or application! Technical data subject to change without notice!

KST8 -U1 -M1 -F3 -LK / KFS11 / V64 / V64.1 / KL / X

Mounting for equipment boxes

V...	Multi-axis Controller (see page 1)
S...	Single-axis Controller (see page 101)
D...	Double-handle Controller (see page 80)
N...	Control-switch (see page 142)
...	More command and indicating devices (see page 218)

Wiring


KL	Without wiring, but terminal block built each terminal
KL V	On terminal block 4 mm ² with single wire 1 mm ² each terminal
KL V	On SPS (SPS provision) with single wire 1 mm ² each terminal
KLVA	External wiring single wire highly flexible 1,5 mm ² , 5 m long each terminal

Special model

X	Special / customer specified
X ²	Special painted

Option

Radio remote control system



* adjustable